

5

10 **METHOD AND APPARATUS FOR PROVIDING
A KEY DISTRIBUTION CENTER WITHOUT
STORING LONG-TERM SERVER SECRETS**

Inventor(s): Radia J. Perlman and Stephen R. Hanna

15

BACKGROUND

Field of the Invention

20 The present invention relates to providing security in communications across computer networks. More specifically, the present invention relates to a method and an apparatus for providing a key distribution center for clients and servers on a computer network that operates without having to store long-term server secrets.

25

Related Art

The advent of computer networks has led to an explosion in the development of applications that transfer information between computer systems across computer networks.

cryptography by storing public keys for users at a KDC, or having users present a certificate.

Unfortunately, performing decryption using a private key is a computationally intensive task, which requires considerably more computational effort than performing decryption using a symmetric key.

What is needed is a method and apparatus for facilitating encryption and decryption that provides the security of using a private key without sacrificing the performance of using a symmetric key.

10

SUMMARY

One embodiment of the present invention provides a system for operating a key distribution center (KDC) that provides keys to facilitate secure communications between clients and servers across a computer network, wherein the system operates without having to store long-term server secrets. The system operates by receiving a communication from a server at the KDC. This communication includes an identifier for the server, as well as a temporary secret key to be used in communications with the server for a limited time period. In response to the communication, the system attempts to authenticate the server. If the server is successfully authenticated, the system stores the temporary secret key at the KDC, so that the temporary secret key can be subsequently used to facilitate communications between a client and the server. Upon subsequently receiving a request at the KDC from a client that desires to communicate with the server, the system produces a session key to be used in communications between the client and server, and then creates a ticket to the server by encrypting an identifier for the client and the session key with the temporary secret key for the server. Next, the system assembles a message that includes the identifier for the server, the session key and the ticket to the server, and sends the message to the client in a

includes a server public key that is associated with a server private key to form a public key-private key pair associated with the server.

In a variation on this embodiment, authenticating the server involves authenticating the server without having prior configuration information
5 pertaining to the server at the KDC.

In a variation on this embodiment, authenticating the server involves using a server public key that is stored locally in the KDC.

In a variation on this embodiment, the temporary secret key is encrypted with a public key belonging to the KDC, so that the temporary secret key can only
10 be decrypted using a private key belonging to the KDC.

In a variation on this embodiment, the communication is signed with a server private key so that the KDC can use a corresponding server public key to verify that the communication was sent by the server.

In a variation on this embodiment, the communication is received in
15 response to a request being sent by the KDC to the server indicating that the temporary secret key is needed from the server.

In a variation on this embodiment, the system additionally communicates information to the server that enables the server to authenticate the KDC.

In a variation on this embodiment, the KDC operates in accordance with
20 the Kerberos standard.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 illustrates a distributed computing system in accordance with an embodiment of the present invention.

25 FIG. 2 illustrates the process of communicating a temporary secret key for a server to a KDC in accordance with an embodiment of the present invention.

FIG. 3 illustrates how the temporary secret key is stored at the KDC in accordance with an embodiment of the present invention.

FIG. 4 illustrates how a client communicates with the KDC in accordance with an embodiment of the present invention.

5 FIG. 5 illustrates how the client communicates with the server in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION

10 The following description is presented to enable any person skilled in the art to make and use the invention, and is provided in the context of a particular application and its requirements. Various modifications to the disclosed embodiments will be readily apparent to those skilled in the art, and the general principles defined herein may be applied to other embodiments and applications without departing from the spirit and scope of the present invention. Thus, the
15 present invention is not intended to be limited to the embodiments shown, but is to be accorded the widest scope consistent with the principles and features disclosed herein.

20 The data structures and code described in this detailed description are typically stored on a computer readable storage medium, which may be any device or medium that can store code and/or data for use by a computer system. This includes, but is not limited to, magnetic and optical storage devices such as disk drives, magnetic tape, CDs (compact discs) and DVDs (digital versatile discs or digital video discs), and computer instruction signals embodied in a transmission medium (with or without a carrier wave upon which the signals are modulated).
25 For example, the transmission medium may include a communications network, such as the Internet.

Distributed Computing System

FIG. 1 illustrates a distributed computing system 100 in accordance with an embodiment of the present invention. Distributed computing system 100 includes clients 104-105, servers 106-107 and key distribution center (KDC) 102 which are all coupled together through network 108.

Network 108 can generally include any type of wire or wireless communication channel capable of coupling together computing nodes. This includes, but is not limited to, a local area network, a wide area network, or a combination of networks. In one embodiment of the present invention, network 108 includes the Internet.

Clients 104-105, servers 106-107 and KDC 102 can generally include any type of computer system, including, but not limited to, a computer system based on a microprocessor, a mainframe computer, a digital signal processor, a portable computing device, a personal organizer, a device controller, and a computational engine within an appliance. Note that KDC 102 may be located on a dedicated computer system, or alternatively, may be hosted on a shared computer system.

Clients 104-105 can generally include any node on network 108 including computational capability and including a mechanism for communicating across the network 108. Note that client 104 is identified with a principal 109 named "Alice". In general, a principal may include a user, a process, a program or any other entity recognized within this system. Also note that a principal need not have a name, such as "Alice", but can instead be identified using some other type of identifier, such as a number. Servers 106-107 can generally include any nodes on network 108 including a mechanism for servicing requests from a client for computational and/or data storage resources. Note that server 106 is identified with a principal 115 named "Bob".

Note that in one embodiment of the present invention, KDC 102 can make use of either a long-term secret, a public key or a short term secret in communicating between KDC 102 and a given principal.

5 In earlier techniques for secure communications between clients and servers using KDCs, a client first obtains a ticket from a KDC, and then communicates with a server using that ticket. In one embodiment of the present invention, we add a new step which is the server establishing a temporary secret key with the KDC. This step typically precedes the other two.

10 **Process of Communicating a Temporary Secret Key to the KDC**

FIG. 2 illustrates the process of communicating a temporary secret key from a server 106 to the KDC 102 in accordance with an embodiment of the present invention.

15 Server 106 and KDC 102 first authenticate each other by exchanging certificate chains and public keys, and using the certificate chains to authenticate each other through a chain of certifying authorities back to a trust anchor. Note that instead of exchanging certificate chains, it is possible for server 106 and KDC 102 to already possess public keys for each other.

20 At the end of this process, Bob holds an authenticated public key, PUB_{KDC} , for KDC 102, and KDC 102 holds an authenticated public key, PUB_B , for Bob.

Note that authenticated communications can alternatively be facilitated by communicating over a secure dedicated network, or by setting up an encrypted pipe for communications, using a protocol such as the secure socket layer protocol (SSL).

25 Server 106 also creates a temporary secret key for Bob, TK_B , and encrypts TK_B with the public key belonging to KDC 102, PUB_{KDC} . Server 106 then creates a message containing an identifier "Bob", the encrypted temporary secret key, EK ,

an expiration time for TK_B , and a key identifier, KEY_ID . Server 106 signs this message with the private key belonging to Bob, $PRIV_B$, and sends the signed message to KDC 102. (Note in the figures that $x[msg]$ represents msg signed with the key x , whereas $x\{msg\}$ represents msg encrypted with the key x .)

5 KDC 102 verifies the signature on the signed message using Bob's public key, PUB_B . Then it decrypts the encrypted temporary secret key, EK , using the KDC's private key, $PRIV_{KDC}$, and stores the identifier, TK_B , KEY_ID , and the expiration time for TK_B , indexed by the identifier "Bob", in database 110 so that TK_B can be used in subsequent communications with Bob.

10 The above-described process is initiated periodically (for example, every hour) by server 106 because each temporary secret key is only valid for a limited time period. Alternatively, the above-described process can be initiated in response to a request for a new temporary secret key generated by KDC 102 whenever KDC 102 requires a new temporary secret key for server 106. In yet a further alternative, KDC 102 can encrypt the ticket to Bob using Bob's public key, and if Bob does not like the overhead of decrypting using the corresponding private key, Bob can establish a temporary secret key with KDC 102. These two alternatives are especially useful when Bob is rarely accessed through KDC 102, since they avoid the overhead of periodically establishing a new temporary secret key.

20 If there are multiple KDCs serving principals 104-107, the multiple KDCs must somehow synchronize the temporary secret key database between themselves, or a server 106 must communicate a temporary secret key to each KDC individually. Note that server 106 may communicate different temporary secret keys with different KDCs.

25 If each KDC has a different secret key, either Bob must perform a trial decryption for each possible secret key, or an identifier for the temporary secret

key must be sent in the clear along with an encrypted message. This identifier enables Bob to determine which temporary secret key to use in decrypting the encrypted message. The identifier is also useful during a transition period shortly after changing Bob's temporary secret key.

5

Storage Structure for Temporary Secret Key

FIG. 3 illustrates how the temporary secret key, TK_B , is stored in database 110 at KDC 102 in accordance with an embodiment of the present invention. For each temporary secret key, database 110 stores a record 300. This record 300
10 includes an identifier 302, a key 304, an expiration time 306 and an ID for the key 308. The identifier 302 can include a character string that identifies a principal, such as "Bob". Key 304 holds the temporary secret key associated with the principal, TK_B . Expiration time 306 specifies an expiration time for TK_B . Finally, the ID for the key 308 specifies an identifier for TK_B .

15 Note that Bob also has to remember the temporary secret key, TK_B , preferably indexed by KEY_ID . In doing so, Bob can use a similar storage structure, possibly without the identifier, "Bob."

Communication Between Client and KDC

20 FIG. 4 illustrates how client 104 communicates with KDC 102 in accordance with an embodiment of the present invention. In this example, a principal 109, Alice, associated with a client 104 requests to login to a server, Bob. Client 104 sends to KDC 102 a request to talk to Bob.

Upon receiving this request, KDC 102 creates a session key, K_{AB} , to be
25 used in communications between Alice and Bob. Next, KDC 102 retrieves Bob's temporary secret key, TK_B , and then creates a "ticket to Bob" by using TK_B to

encrypt the identifier for "Alice" and K_{AB} , and by attaching the key identifier for TK_B , KEY_ID , in the clear.

KDC 102 then creates a message containing an identifier "Bob", K_{AB} , and the ticket to Bob, and then encrypts the message using the master key for Alice, S_A (a function of Alice's password), before sending the message to client 104. Upon receiving this message, client 104 decrypts it using S_A to restore the identifier, "Bob", K_{AB} , and the ticket to Bob.

Communication Between Client and Server

FIG. 5 illustrates how client 104 communicates with server 106 after receiving the encrypted message from KDC 102 in accordance with an embodiment of the present invention.

In order to facilitate communications between Alice and Bob, client 104 sends the ticket to Bob to server 106. Server 106 uses the key identifier KEY_ID , to look up the temporary secret key, TK_B . Server 106 then uses TK_B to decrypt the ticket to Bob to restore K_{AB} and "Alice". Server 106 subsequently uses K_{AB} in communications with client 104. If client 104 can prove it knows K_{AB} , Bob will know client 104 is associated with Alice.

Note that additional steps dealing with time stamps have been omitted from the above discussion related to FIGs. 4-5.

Also note that from Alice's perspective nothing changes in the process outlined in FIGs. 4 and 5 from standard Kerberos, because Alice is oblivious as to whether a temporary secret key or a permanent secret key is used to encrypt the ticket to Bob. Only KDC 102 and server 106 need to be aware of the fact that a temporary secret key has been used instead of a permanent secret key.

Additionally, note that Alice can use a TGT in communicating with the KDC.

The foregoing descriptions of embodiments of the invention have been presented for purposes of illustration and description only. They are not intended to be exhaustive or to limit the present invention to the forms disclosed.

Accordingly, many modifications and variations will be apparent to practitioners skilled in the art. Additionally, the above disclosure is not intended to limit the present invention. The scope of the present invention is defined by the appended claims.